



### AQUA LOGIC HEAT EXCHANGERS

MODEL #	NOMINAL HP	*NOMINAL BTUH/KW	A	B	WATER FLOW RATE MIN/MAX. (GPM)	WATER CONNECTION INLET/OUTLET (INCH)	REFRIGERANT CONNECTION HIGH/LOW (ODF)
HX-2DX	1/5	1,800/.5	12"	20"	6/12	3/4	3/8 / 3/8
HX-3DX	1/4	3,000/.8	12"	20"	8/15	3/4	3/8 / 3/8
HX-4DX	1/3	4,000/1.2	12"	22"	10/20	3/4	3/8 / 3/8
HX-6DX	1/2	6,000/1.8	12"	23"	12/25	1 1/2	3/8 / 1/2
HX-9DX	3/4	9,500/2.6	16"	30"	20/35	1 1/2	3/8 / 1/2
HX-12DX	1	12,000/3.5	16"	33"	25/40	1 1/2	3/8 / 5/8


 Aqua Logic, Inc.  
 8268 Clairemont Mesa Blvd. Suite 302  
 San Diego, CA 92111

TITLE: HX-3DX thru HX-12DX  
 Specifications, 24V  
 Control

LAST UPDATE: 3-15-07

DATE: 7-2-03

FILE: HX-3DX thru HX-18DX Dem 2

BY: CE