


HEAT EXCHANGER SPECIFICATIONS				
MODEL NO.	NOMINAL BTUH/TONS/KW	REFRIGERANT CONNECTIONS LIQUID/SUCTION (ODF)	WATER FLOW MIN*/MAX (GPM)	DIM "H"
HX-90-S	90K / 7.5 / 26.3	3/4" / 1 5/8"	90/180	60
HX-120-S	120K / 10 / 35	3/4" / 1 5/8"	90/180	66
HX-140-S	140K / 12.5 / 41	3/4" / 1 5/8"	90/180	72
HX-180-S	175K / 15 / 51.2	3/4" / 1 5/8"	90/180	80
HX-240-S	220K / 20 / 64.4	3/4" / 1 5/8"	90/180	88

* MINIMUM FLOW RATE AT 65 F AND ABOVE. AT 65 F AND BELOW 120 GPM MINIMUM
 ALL DEMINIONS ARE APPROXIMATIONS AND MAY CHANGE AT ANY TIME
 50 PSI MAXIMUM WATER PRESSURE
 400 PSI MAXIMUM REFRIGERANT PRESSURE

 Aqua Logic, Inc.
 8288 Clairemont Mesa Blvd. Suite 302
 San Diego, CA 92111

TITLE: SINGLE CIRCUIT HX-90-S
 THRU HX-240-S HEAT
 EXCHANGERS

LAST UPDATE: 10-17-06

DATE: 4-22-05

FILE: HX-90 THRU 240-S

BY CE